


# Advance SX 2

## Premium two-stroke motorcycle oil



Advance SX 2 is a premium quality oil blended for on-highway two-stroke motorcycle engines. High viscosity index mineral oils, fortified by polyisobutylene synthetic base fluid, combine with carefully selected additives to produce a superior performance oil for today's two-stroke motorcycles.

### Applications

- Two-stroke motorcycle engines with oil injection or premix system.

*Advance SX 2 should not be used in outboard engines. The appropriate Nautilus Oil is recommended for this application.*

### Performance Features

- *Reduced smoke*
- *Extra power and smoother performance*
- *Good engine cleanliness*
- *Longer engine life*
- *Self-mixing with leaded and unleaded petrol*

### Performance Level

JASO FB

ISO EGB

Advance SX 2 meets industry specifications for two-stroke oils.

### Self-Mixing Properties

Advance SX 2 is a self-mixing oil containing hydrocarbon diluent. It is blended to the correct viscosity for use in oil injection systems fitted to modern two-stroke motorcycles.

### Health & Safety

Advance SX 2 is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

Avoid contact with skin. After skin contact, wash immediately with soap and water.

For further guidance on Product Health & Safety refer to the appropriate Shell Product Safety Data Sheet.

### Typical Physical Characteristics

Advance	SX 2
<b>Kinematic Viscosity</b> @ 40°C cSt 100°C cSt (IP 71)	<b>Undiluted</b>  - 7.4
<b>Density @ 15°C kg/l</b> (IP 365)	0.896
<b>Flash Point °C</b> (Cleveland Open Cup) (IP 36)	102
<b>Pour Point °C</b> (IP 15)	-30

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

### Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.

